

SERVICE AT A GLANCE MAINTENANCE INTERVALS FOR PINNACLE™, GRANITE®, TERRAPRO®, AND ANTHEM™ MANUFACTURED YEAR 2022 GHG AND NEWER

		Economy Duty Greater than 7.5 mpg Less than 31L/100km	Normal Duty Greater than 6 mpg Less than 39L/100km	Heavy Duty Greater than 5 mpg Less than 50L/100km	Severe Duty Less than 5 mpg Greater than 50L/100km	
ENGINE						
MACK PREMIUM ENGINE OIL, FILTERS AND FUEL FILTERS Manufactured Year 2022 GHG and Newer Engines Using Mack EOS-5 O NOTE: Mack cannot be held responsible for problems caused by non-genuine filters that de *Mack Engine Oil EOS-5 / **Other Mack Approved EOS-5 Oil	_		ırability requirements.			
MP7 / MP8 Oil Pan: Mack EOS-5, Filters and Fuel Filters (Replace) If idle time is greater than 30%, use the next lower drain interval.	Miles	75,000* / 55, 000**	60,000* / 55,000**	45,000* / 40,000**	35,000* / 30,000**	
Note: Actual fuel filter service intervals may vary based on fuel quality and vehicle application. For additional information, reference service document 170/Description, Design and Function/Diesel Fuel.		120,000* / 90,000**	95,000* / 90,000**	70,000* / 65,000**	55,000* / 50,000**	
Note: VAH low capacity oil pan oil drain interval is 20,000 miles. Use severe duty category for all filters.	Hours	2,000* / 1,600**	1,700* / 1,600**	1,400* / 1,300**	825* / 750**	
MACK PREMIUM EXTENDED-LIFE COOLANT						
Mack Premium Extended-Life Coolant (Replace)	Miles Km Hours	750,000 1.200,000 96 months				
	Miles	150,000				
Mack Premium Extended-Life Coolant Filter (Replace)	Km	240,000				
	Time	12 months				
MISCELLANEOUS	Miles		150 000 / then	every 300 000		
Valve and Injector Adjustment	Km	150,000 / then every 300,000 240,000 / then every 500,000				
	Time		12 months / then every 24 months			
Fan and Accessory Drive Belt and Tensioners (Replace)	Miles	450,000	360,000	315,000	210,000	
	Km	724,000	579,000	506,000	337,000	
Mack Premium Air Filter and Fuel Tank Ventilation Filter (Replace)	Time	Inspect at each oil drain. Replace at max restrictions as indicated on gauge or 24 months.			Inspect at each oil drain. Replace at max restrictions as indicated on gauge or 12 months	
EXHAUST AFTERTREATMENT SYSTEM		Economy Duty	Normal Duty	Heavy Duty	Severe Duty	
Diesel Particle Filter (DPF) - Clean	Miles	600,000	480,000	405,000	280,000	
	Km	965,000	772,000	650,000	450,000	
	Hours	15,000	12,000	10,000	5,000	
DEF, Pump and Tank Filler Neck Filter Drain DEF tank, replace DEF pump main filter, clean DEF tank neck filter.	Miles	300,000 482,000	240,000 386,000	180,000 289,000	175,000 280,000	
	Hours	9,000	7,000	5,500	5,200	
TRANSMISSION AND AXLES		Economy Duty	Normal Duty	Heavy Duty	Severe Duty	
MACK <i>m</i> DRIVE™ TRANSMISSION						
mDRIVE; mDRIVE Severe Duty* and mDRIVE with Crawler Gears*						
Transmission oil and filter (Replace)	Miles	525,000 500,000		250,000*		
Oil quality: Mack Transmission Oil 97319	Km	844,000	800	,000	400,000*	
*Applies for mDRIVE severe duty and mDRIVE with Crawler Gears only	Time	60 months 2,500 hours				
AXLES			250,000 (GO-J)		40,000,(00,1)	
Mack Proprietary Rear Axle Oil (Replace)	Miles		500,000 (GO-J PLUS) 80,000 (GO-J 400,000 (GO-J) 65,000 (GO		40,000 (GO-J) 80,000 (GO-J PLUS) 65,000 (GO-J)	
	Time		24 months (GO-1)		125,000 (GO-J PLUS) 1200 hours or 12 months	
Vendor Rear Axle Oil (Replace)			See axle manufacturer guidelines			
Steer and Drive Axle Alignment	Time		12 months	(minimum)		
CHASSIS		Economy Duty	Normal Duty	Heavy Duty	Severe Duty	
Mack Premium Chassis Lubrication	Miles		15,000 24,000			
Electrical System Connectors (Check)	Time		Every 6	months		
Power Steering Fluid and Filter (Replace)	Miles Km	150,000 240,000				
Air Druge Coologging Cortridge (Donlogs)	Time Miles Km	12 months 150,000 240,000				
Air Dryer Coalescing Cartridge (Replace)	Time		12 months			
These maintenance intervals are general recommendations. Please refer to the appropriate maintenance and lubrication manual for your specific vehicle as the authoritative		letails of a proper and complete inspection and n			curs first.	

PV960-M-SAAG-22-010423